CLAIMS

What is claimed is:

1. A removable security post assembly, comprising:

an anchorage assembly positioned below ground level and including first housing means having first and second ends and said first end being an opening adjacent to the ground level, and said anchorage assembly further includes anchorage means rigidly mounted to said first housing means, and wherein said first housing means has at least one bay member that is outwardly and perpendicularly projected with respect to said first housing means,

an elongated post member removably and partially received within said first housing means, said elongated post member is tubular having third and fourth opened ends, and said elongated post member further includes at least one lateral opening, that once the former is placed inside said first housing means, said lateral opening is in horizontal alignment with said bay member, and

- a locking assembly including a lock for securing said elongated post member to said anchorage assembly, said locking assembly is mounted to said third opened end.
 - 2. The removably security post assembly set forth in claim 1 wherein said lock is rigidly mounted to second housing means that in turn slides inside said clongated post member adjacent to said third opened end.
- 3. The removably security post assembly set forth in claim 2 wherein said second housing means includes cable means extended and holding at its distal end a latching member.

إزإ

- 4. The removably security post assembly set forth in claim 3 wherein said latching member includes latching means inserted in said bay member through said lateral opening so that said elongated post member is firmly anchored to said anchorage assembly.
- 5. The removably security post assembly set forth in claim 1 wherein said anchorage assembly further includes drainage means through which the water trapped inside said first housing means flows away.

A2 6. The removably security post assembly set forth in claim 1 wherein said anchorage assembly further includes means for covering said opening of said first housing means, once said elongated post member is removed from the ground.